
HYDRAULIC ROBOT

HYDRA-MP3





HYDRA-MPseries are six DOF(degree of freedom) robot manipulators. It was designed to provide high flexibility for robot applications.

MP3 finally looks like a motor-based manipulator by virtue of its invisible hose outside of the actuators and links.

DOF

Payload

Actuator

Weight

Joint Sensor

Servo Valve

6

70 kg(at 210bar)

Hydraulic Rotary Type

90kg

19bit absolute encoder

STAR, model-700

SPECIFICATIONS	

	J1	J2	J3	J4	J5	J6
Motion Range(degree)	-50 ~ 50	-105 ~ -5	-50 ~ 50	-105 ~ -5	-50 ~ 50	5 ~ 105
Actuator	RH300	RH300	RH500	RH500	RH1000	RH1000
Max. Torque(Nm)	300	300	500	500	1,000	1,000



SYSTEM CONFIGURATION



LCU (Limb Control Unit)

- Hard Realtime(1kHz
- FK IK Kinematics and Jacobian
- UDP/CAN Communication
- Analog signal In/Out





Simulator/Interface



HAC (Hydraulic Actuator Controller)

- Hard Realtime(5kHz)
- PID. Force Control
- CAN Communication
- Analog signal Input
- PWM signal Output





